



Metal Frame LCD Monitor

# MA121

- 12.1" SVGA / XGA TFT LCD with resolution up to 800 x 600 / 1024 x 768.
- Suitable for military, tablet, ruggedized PC, kiosk, advertising, POS, marine, transportation, gaming, gas pump.



## SPECIFICATIONS

Model Name	Display Resolution (pixel)	Display Color	Viewing Angle (CR ≥ 10) (R/L/U/D)	Brightness (cd/m <sup>2</sup> )	Contrast Ratio	Backlight Unit	Response Time (msec)
MA121N1	SVGA(800x600)	262K / 16.2M	80 / 80 / 50 / 60	400	600:1	CCFL	35
MA121S1	SVGA(800x600)	262K / 16.2M	80 / 80 / 50 / 60	1000	600:1	LED	35
MA121N2	SVGA(800x600)	262K / 16.2M	80 / 80 / 65 / 75	450	700:1	LED	35
MA121N3	XGA(1024x768)	262K / 16.2M	80 / 80 / 80 / 80	500	700:1	LED	35

Note: Fanless: Brightness < 1000 cd/m<sup>2</sup> ;  
Add fan: Brightness ≥ 1000 cd/m<sup>2</sup>

## ORDER INFORMATION


### MA121XX - X X X X

①                      ②   ③   ④   ⑤

① Model Name		④ Signal Input	C: VGA. D: VGA + DVI-D. E: VGA + DVI-D + Audio. J: VGA + DVI-I + Audio + HDMI. L: VGA + S-Video + CVBS.
② Mounting / Stand	N: No accessories.		
③ Touch Screen	N: No Touch screen or glass. G: Glass. R: Resistive, RS232 interface. U: Resistive, USB interface.	⑤ Other	

## DIMENSIONS

Unit:mm



## ACCESSORIES

Power Cord		VGA Cable	
R003OF180G003	Power Cord US Type L=1.8m	R003OH180G004	DB15p, Male/Male, L=1.8m
R003OF180G004	Power Cord German Type /2P L=1.8m	R003OH300G001	DB15p, Male/Male, L=3.0m
R003OF180G005	Power Cord UK Type /3P L=1.8m	R003OH500G001	DB15p, Male/Male, L=5.0m
Adapter			
R007W05002512	DC Adapter 12V 50W 4.16A		